


Specifications:

Type	PLP 10.1	PLP 10.2	PLP 10.2,5	PLP 20.6,3	PLP 20.8
Displacement (cm ³ /cycle)	1	2	2.5	6.5	8.3
Max. continuous pressure (bar)	260	260	260	250	250
Max. intermittent pressure (bar)	280	280	280	280	280
Max. peak pressure (bar)	300	300	300	300	300
Max. speed (rpm)	4000	4000	4000	4000	3500

Dimensions:

Type	PLP 10.1	PLP 10.2	PLP 10.2,5	PLP 20.6,3	PLP 20.8
A	74	74	74	102	102
B	65	65	65	87	87
C	51.7	54.9	56.5	77.5	80.1
E	17.6	19.2	20	27	28.3
F	11.3	11.3	11.3	16	16
G	72	72	72	89.5	89.5
H	∅ 7	∅ 7	∅ 7	∅ 9	∅ 9
I	89	89	89	114.2	114.2
J	72	72	72	96.2	96.2
K	52	52	52	71.5	71.5
L	26.5	26.5	26.5	32.2	32.5

Ordering:

DMS order no.:	Type:
320-1201	PLP 10.2D
320-1202	PLP 20.6,3D
320-1203	PLP 20.8D
320-1204	PLP 10.1D
320-1205	PLP 10.2,5D

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.