

Mounting interface: ISO 4401 size 03
 ANSI/B93.7M size D03
 CETOP RP65H size 3
 DIN 24340 NG6
 IEC 144 - IP65

Ordering:

Coil rating:	DSH-order-no:	Type:	Symbol:
115 V/ 60 Hz 230 V/ 60 Hz 220 V/ 50 Hz 24 V DC	344-0711 344-0712 344-0714 344-0717	DG4V-3-2C-H-MU1EK6-60-EN38 DG4V-3-2C-H-MU1D6-60-EN38 DG4V-3-2C-H-MU1C6-60-EN38 DG4V-3-2C-H-MU1H7-60-EN38	
115 V/ 60 Hz 230 V/ 60 Hz 220 V/ 50 Hz 24 V DC	344-0731 344-0732 344-0734 344-0737	DG4V-3-6C-H-MU1EK6-60-EN38 DG4V-3-6C-H-MU1D6-60-EN38 DG4V-3-6C-H-MU1C6-60-EN38 DG4V-3-6C-H-MU1H7-60-EN38	
115 V/ 60 Hz 230 V/ 60 Hz 220 V/ 50 Hz 24 V DC	344-0801 344-0802 344-0804 344-0807	DG4V-3-2N-H-MU1EK6-60-EN38 DG4V-3-2N-H-MU1D6-60-EN38 DG4V-3-2N-H-MU1C6-60-EN38 DG4V-3-2N-H-MU1H7-60-EN38	
115 V/ 60 Hz 230 V/ 60 Hz 220 V/ 50 Hz 24 V DC	344-0811 344-0812 344-0814 344-0817	DG4V-3-2A-H-MU1EK6-60-EN38 DG4V-3-2A-H-MU1D6-60-EN38 DG4V-3-2A-H-MU1C6-60-EN38 DG4V-3-2A-H-MU1H7-60-EN38	
230 V/ 50 Hz 220 V/ 50 Hz 24 V DC 12 V DC	344-0822 344-0824 344-0827 344-0828	DG4V-3-2AL-H-MU1D6-60-EN38 DG4V-3-2AL-H-MU1C6-60-EN38 DG4V-3-2AL-H-MU1H7-60-EN38 DG4V-3-2AL-H-MU1G7-60-EN38	

Accessory:

DSH order-no.:	Type:	Description:
INT-1564	4099-0422	Latching manual override